



## Basis Geometrie

	XS	S	M	L	XL
Körpergrösse in cm	≤ 166	166 - 175	175 - 183	183 - 192	≥ 192
Sitzhöhe in mm (a)	583 - 733	623 - 773	663 - 813	703 - 853	743 - 893
Sitzrohlänge in mm (b)	375	415	455	495	535
Oberrohrlänge in mm (c)	564	581	602	625	648
Steuerrohr in mm (d)	90	90	95	110	125
Lenkwinkel (e)	68,5°	68,5°	68,5°	68,5°	68,5°
Sitzrohrwinkel (f)	75°	75°	75°	75°	75°
Kettenstreben in mm (g)	432	432	432	432	432
Radstand in mm (h)	1.100	1.120	1.142	1.167	1.193
Stack in mm (i)	577	577	582	596	610
Reach in mm (j)	410	430	450	470	490
Überstandshöhe in mm (k)	777	777	780	784	793
Tretlager-Offset in mm (l)	38	38	38	38	38

## Dimensionen Anbauteile

	XS	S	M	L	XL
Spacer in mm	0,0	10,0	10,0	15,0	20,0
Vorbaulänge in mm	70	70	70	70	70
Lenkerbreite in mm	740	740	740	740	740
Kurbellänge in mm	170,0	170,0	175,0	175,0	175,0
Kettenblattgrösse	34	34	34	34	34
Sattelstütze Ø in mm	30,9	30,9	30,9	30,9	30,9
Sattelstützenlänge in mm	400	400	400	400	400
Maximale Einschubtiefe der Sattelstütze in mm	240	240	240	240	240
Minimale Einschubtiefe der Sattelstütze in mm	90	90	90	90	90
Laufgradgrösse	29"	29"	29"	29"	29"
Durchmesser Bremsscheibe in mm	180 / 160	180 / 160	180 / 160	180 / 160	180 / 160
Federweg vorne in mm	100	100	100	100	100
Federweg hinten in mm	100	100	100	100	100
Einbaulänge in mm	210X50	210X50	210X50	210X50	210X50