



## Spank Industries EVO Rim Line - Technical Data Sheet

	Stiffy 40AL EVO	Spike 35AL EVO	Spike Race28 EVO	Spoon	Subrosa Evo-26"	Subrosa Evo-29"	Subrosa EVO-650b/27.5"
Extreme Outer Diameter	OD 568.7mm	OD 568.6mm	OD 568.7mm	OD 570.6mm	OD 568.7mm	OD 632mm	OD 594mm
Category*	Extreme FR/DH	DH/FR	DH / FR / All MTN	DH/FR	All MTN/Lite-FR	All MTN/Lite-FR	All MTN/Lite-FR
ETRTO	559 x 34.3	558.9 x 29.45	559 x 22mm	559 x 26.7	559 x 24.5	622X24.5	584X24.5
ERD	530mm	530mm	531.8mm	530mm	530mm	589mm	550.5+mm
Width	40mm	35mm	28mm	32mm	30mm	30mm	30mm
Width (Inner)	34.3mm	29.45mm	23mm	26.7mm	24.5mm	24.5mm	24.5mm
Sectional Depth	22.95mm	22.95mm	22mm	24mm	23.5mm	23.5mm	23.5mm
Spoke Hole Configuration	32H	32H	32H	32H	32H	32H	32H
Valve holes	8.5mm A/V (Shrader)	6.5mm F/V (Presta)	6.5mm F/V (Presta)	6.5mm A/V (Presta)	6.5mm F/V (Presta)	6.5mm F/V (Presta)	6.5mm F/V (Presta)
Weight **	Anodized	575g	595g	600g	515g	610g	555g
	Liquid Coat	690g	610g	X	530g	625g	570g
Material	Super-6	Dynamal	Dynamal	6061	Dynamal	Dynamal	Dynamal
Oohbah Techonology	yes	yes	yes	yes	yes	yes	yes
BeadNip	yes	yes	yes	yes	yes	yes	yes
Orbital Nipple Seat	yes	yes	yes	yes	yes	yes	yes
Hoop Joint	Sleeved	Sleeved	Sleeved	Pinned	Sleeved	Sleeved	Sleeved
SideWall	Disc	Disc	Disc	Disc	Disc	Disc	Disc
Rim Tape	20mm White	20mm White	16mm Black	16mm Black	16mm Black	16mm Black	16mm Black
Rec.Tire Width Min	26"x2.1"	26x 2"	26" x 1.9"	26x2"	26 x 1.9"	29 x 1.9"	29 x 1.9"
Rec.Tire Width Max	26"x 3"+	26"x 3"	26" x 2.5"	26"x 3.0	26 x 2.5"	29 x 2.5"	29 x 2.5"
Tire pressure Max***	3 bar	3 bar	3 bar	3 bar	3 bar	3 bar	3 bar
Rec. Max Rider weight	150kg	120kg	110 kg	120kg	110kg	100kg	110 kg

\* Refer to recommended usage table

	Tweet-28	Oozy EVO-26"	Oozy EVO-29"/700c	Oozy EVO-650b/27.5"	Vomax	Vomax 29"/700c
Extreme Outer Diameter	OD 570.6mm	OD 568.7mm	OD 632mm	OD 594mm	OD 568.65mm	632
Category*	Dirt/Park/Street	Aggressive Trail/XC	XC / Trial / Xcross/ Fixie	Aggressive Trail/XC	XC Race	XC / Trial / Xcross / Fixie
ETRTO	559 x 22.9	559 x 21	622X21	584X21	559 x 18.5	622x18.5
ERD 26"	530mm	534mm+/-	597mm+/-	558.5+mm	537.5mm	598mm
Width	28mm	26mm	26mm	26mm	23mm	23mm
Width (Inner)	22.9mm	21mm	21mm	21mm	18.5mm	18.5mm
Sectional Depth	24mm	19.25mm	19.25mm	19.25mm	19mm	19mm
Spoke Hole Configuration	32H	32H/28H	32H/28H	32H/28H	32H/28H	32H/28H
Valve holes	8.5mm A/V (Shrader)	6.5mm F/V (Presta)	6.5mm P/V (Presta)	6.5mm P/V (Presta)	6.5mm P/V (Presta)	6.5mm P/V (Presta)
Weight **	Anodized	590g	420g	480g	360g	425g
	Liquid Coat	X	430g	500g	360g	435g
Material	6061	Dynamal	Dynamal	Dynamal	Dynamal	Dynamal
Oohbah Techonology	yes	yes	yes	yes	yes	yes
BeadNip	yes	yes	yes	yes	yes	yes
Orbital Nipple Seat	yes	yes	yes	yes	yes	yes
Hoop Joint	Pinned	Sleeved	Sleeved	Sleeved	Flash Welded	Flash Welded
SideWall	Disc	Disc	Disc	Disc	Disc	Disc
Rim Tape	16mm Black	13mm Red	13mm Red	13mm Red	13mm Red	13mm Red
Rec.Tire Width Min	26x1.75"	29"x 1.5"	29"x 1.5"	29"x 1.5"	26"x 1.0"	29"x 1.0"
Rec.Tire Width Max	26 x 2.5"	26"x 2.35"	29"x 2.35"	29"x 2.35"	26"x 2.35"	29"x 2.35"
Tire pressure Max***	4 bar	4 bar	4 bar	4 bar	4 bar	4 bar
Rec. Max Rider weight	110kg	100kg	90 kg	90 kg	90kg	80kg

DYNAMAL  
ALLOY

SUPER 6  
MILMM



Frattelli  
Industries