

STUMPJUMPER 15 COMP



Gloss Seafoam / Silver Dust



Satin Burnt Gold / Gunmetal

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis and rear-end
- Robust Specialized alloy wheels with sealed cartridge bearings
- Ride Dynamics tuned FOX FLOAT Performance Elite with Specialized GENIE patent-pending air spring technology provides maximum grip and traction found in a linear coil spring, bottom-out prevention found in a progressive air spring, and the ability to tune mid-stroke and end-stroke support independently. Highly adjustable 2-position open and firm mode with the 3-position open mode compression adjuster.
- Eat up the chunkiest trails with the FOX FLOAT 36 Rhythm fork with GRIP damper
- Smooth and precise shifting from SRAM Eagle T-Type AXS drivetrain
- Big braking power from SRAM Maven Bronze 4-piston brakes
- Trustworthy time and time again X-Fusion Manic dropper post
- Lifetime bearing replacement

STUMPJUMPER 15 COMP	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Headtube Length (mm)	95	100	110	125	140	155
Headtube Angle (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Fork Length (full) (mm)	551	561	561	561	561	561
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	720	751	780	812	843	879
Chainstay Length (mm)	430	432	435	435	445	445
Wheelbase (mm)	1149	1181	1213	1244	1285	1322
Top-tube Length (horizontal) (mm)	541	573	595	624	647	677
Bike Standover Height (mm)	738	751	745	745	745	751
Seat Tube Length (mm)	385	385	405	425	445	465
Seat Tube Angle (degrees)	77	76.5	77.2	76.9	77.3	77.6
Max Seatpost Insertion (mm)	245	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	165	165	165	170	170	170
Handlebar Width (mm)	780	780	800	800	800	800
Stem Length (mm)	40	40	40	40	40	40
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	125	150	170	190	190	190

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	FOX FLOAT Performance with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/ LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
FORK	FOX FLOAT 36 Rhythm, GRIP damper, two position Sweep adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
STEM	Alloy Trail Stem, 35mm bar bore
GRIPS	Specialized Trail Grips
SADDLE	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
HANDLEBARS	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
FRONT BRAKE	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
REAR BRAKE	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm
SHIFT LEVERS	SRAM AXS POD Controller
REAR DERAILLEUR	SRAM S1000 Eagle Transmission Derailleur
CASSETTE	SRAM XS-1270 Transmission Cassette, 12spd, 10-52t
CHAIN	SRAM GX Eagle Transmission Flattop Chain
CRANKSET	SRAM S1000 Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
BOTTOM BRACKET	SRAM DUB, BSA 73mm Wide, Threaded
RIMS	Specialized, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2:27.5, S3-S6:29
FRONT HUB	Alloy, sealed cartridge bearings, 15x110mm thru-axle, 28h
REAR HUB	Alloy, sealed cartridge bearings, 12x148mm thru-axle, 28h
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
SPOKES	DT Swiss Industry
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
INNER TUBES	Standard, Presta valve
SEATPOST	X-Fusion Manic, infinite adjustable, two-bolt head, bottom mount cable routing, remote SLR LE lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 190mm
SEAT BINDER	Alloy, 38.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
93325-5001	SJ 15 COMP SEA/SILDST S1	Gloss Seafoam / Silver Dust	S1 29/27.5
93325-5002			S2 29/27.5
93325-5003			S3 29
93325-5004			S4 29
93325-5005			S5 29
93325-5006			S6 29
93325-5101	SJ 15 COMP BNTGLDMET/GUN S1	Satin Burnt Gold / Gunmetal	S1 29/27.5
93325-5102			S2 29/27.5
93325-5103			S3 29

STUMPJUMPER 15 COMP

PART NO.	DESCRIPTION	COLOR	SIZE
93325-5104	SJ 15 COMP BNTGLDMET/GUN S4	Satin Burnt Gold / Gunmetal	S4 29
93325-5105			S5 29
93325-5106			S6 29

STUMPJUMPER 15 OHLINS COIL



IMAGE
coming soon

Satin Copper Speckle / Satin Silver Dust

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis and rear-end
- Incredibly tough Roval Traverse wheels with DT Swiss 370 hub
- Premium suspension support from an Öhlins TTX 22 M Coil, Ride Dynamics tuned
- Plow through anything with a 160mm Öhlins RXF38 M.2 29 fork
- Reliable and smooth shifting from SRAM GX Eagle AXS T-Type drivetrain
- Powerful brakes with great hand feel thanks to TRP DH-R EVO 4-piston brakes
- Adjustable travel PNW LOAM dropper post
- Lifetime bearing replacement

STUMPJUMPER 15 OHLINS COIL

	S2	S3	S4	S5	S6
Stack (mm)	621	630	644	657	671
Reach (mm)	420	445	470	495	525
Headtube Length (mm)	100	110	125	140	155
Headtube Angle (degrees)	64	64	64	64	64
BB Height (mm)	340	340	340	340	340
BB Drop (mm)	35	35	35	35	35
Trail (mm)	134	134	134	134	134
Fork Length (full) (mm)	573	573	573	573	573
Fork Rake/Offset (mm)	44	44	44	44	44
Front Center (mm)	755	785	816	848	884
Chainstay Length (mm)	432	432	432	442	442
Wheelbase (mm)	1186	1216	1247	1288	1325
Top-tube Length (horizontal) (mm)	574	596	625	649	678
Bike Standover Height (mm)	751	745	745	745	751
Seat Tube Length (mm)	385	405	425	445	465
Seat Tube Angle (degrees)	76	76.5	76.5	76.8	77.2
Max Seatpost Insertion (mm)	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80
Crank Length (mm)	165	165	170	170	170
Handlebar Width (mm)	810	810	810	810	810
Stem Length (mm)	35	35	35	35	35
Saddle Width (mm)	155	143	143	143	143
Seatpost Length (mm)	150	170	200	200	200

SPECS Specifications subject to change without notice.

FRAME	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	Öhlins TTX 22 M Coil, Ride Dynamics trail tune, external rebound adjust, external high and low speed compression adjustment, 210x55
FORK	Öhlins RXF38 M.2 29, TTX Twin Tube Damping, external low speed rebound adjust, external high and low speed compression adjustment, 15x110mm, 44mm offset, 160mm of travel
STEM	Deity, 35mm clamp, 35mm length
SADDLE	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
HANDLEBARS	Deity, Racepoint, 5-degree upsweep, 9-degree backsweep, 810 width, S2: 25mm rise; S3-S6: 38mm rise
FRONT BRAKE	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 220mm
GRIPS	Diety, Supracush, Black
REAR BRAKE	TRP DH-R EVO, 4-piston caliper, hydraulic disc, 203mm
SHIFT LEVERS	SRAM AXS POD Controller
REAR DERAILLEUR	SRAM GX Eagle Transmission Derailleur
CASSETTE	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
CHAIN	SRAM GX Eagle Transmission Flattop Chain
CRANKSET	SRAM GX Eagle Crankset, 32T ring, 55mm Chainline, S2-S3:165mm, S4-S6: 170mm
BOTTOM BRACKET	SRAM DUB, BSA 73mm Wide, Threaded
RIMS	Roval Traverse, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: 27.5
FRONT HUB	DT Swiss 370, 15x110mm, 28h
REAR HUB	DT Swiss 370, 12x148mm, 32h
SPOKES	Sapim Force
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
REAR TIRE	Eliminator, GRID GRAVITY casing, GRIPTON® T9/T7 compound, 2Bliss Ready, 27.5x2.3"
INNER TUBES	Standard, Presta valve
SEATPOST	PNW Loam OE Dropper, tool-less travel adjust, Range lever, 34.9, S2: 150mm, S3: 170mm, S4-S6: 200mm
SEAT BINDER	Alloy, 38.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
93325-7502	SJ 15 OHLINS COILCOP/SILDST S2	Satin Copper Speckle / Satin S	S2
93325-7503			S3
93325-7504			S4
93325-7505			S5
93325-7506			S6

STUMPJUMPER 15 EXPERT



Gloss Gunmetal / White Mountains



Satin Electric Green / Satin Forest Green

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis and rear-end
- Ride Dynamics tuned FOX FLOAT Performance Elite with Specialized GENIE patent-pending air spring technology provides maximum grip and traction found in a linear coil spring, bottom-out prevention found in a progressive air spring, and the ability to tune mid-stroke and end-stroke support independently. Highly adjustable 2-position open and firm mode with the 3-position open mode compression adjuster.
- Supportive and tuneable FOX FLOAT 36 Performance Elite fork with GRIP X2 damper
- Strong and trusted Roval Traverse wheels, DT Swiss 370 hub
- Smooth and precise SRAM GX Eagle T-Type AXS drivetrain
- Powerful and reliable SRAM Maven Bronze 4-piston brakes
- Adjustable travel with PNW LOAM dropper post
- Lifetime bearing replacement

STUMPJUMPER 15 EXPERT	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Headtube Length (mm)	95	100	110	125	140	155
Headtube Angle (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Fork Length (full) (mm)	551	561	561	561	561	561
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	720	751	780	812	843	879
Chainstay Length (mm)	430	432	435	435	445	445
Wheelbase (mm)	1149	1181	1213	1244	1285	1322
Top-tube Length (horizontal) (mm)	541	573	595	624	647	677
Bike Standover Height (mm)	738	751	745	745	745	751
Seat Tube Length (mm)	385	385	405	425	445	465
Seat Tube Angle (degrees)	77	76.5	77.2	76.9	77.3	77.6
Max Seatpost Insertion (mm)	245	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	165	165	165	170	170	170
Handlebar Width (mm)	780	780	800	800	800	800
Stem Length (mm)	40	40	40	40	40	40
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	125	150	170	200	200	200

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	FOX FLOAT Performance Elite with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
FORK	FOX FLOAT 36 Performance Elite, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
STEM	Alloy Trail Stem, 35mm bar bore
SADDLE	Bridge Comp, Hollow Cr-mo rails, S1-S2: 155mm, S3-S6: 143mm
HANDLEBARS	Specialized, 6000 series alloy, 6-degree upsweep, 8-degree backsweep. S1-S2: 780 width, 20mm rise; S3-S4: 800 width, 30mm rise; S5-S6: 800 width, 40mm rise
GRIPS	Deity Lockjaw
FRONT BRAKE	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, 200mm
REAR BRAKE	SRAM Maven Bronze, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm
SHIFT LEVERS	SRAM AXS POD Controller
REAR DERAILLEUR	SRAM GX Eagle Transmission Derailleur
CASSETTE	SRAM GX Eagle Transmission Cassette, 12spd, 10-52t
CHAIN	SRAM GX Eagle Transmission Flattop Chain
CRANKSET	SRAM GX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
BOTTOM BRACKET	SRAM DUB, BSA 73mm Wide, Threaded
RIMS	Roval Traverse, hookless alloy, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2: 27.5, S3-S6: 29
FRONT HUB	DT Swiss 370, 15x110mm, 28h
REAR HUB	DT Swiss 370, 12x148mm, 28h
SPOKES	Sapim Force
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
INNER TUBES	Standard, Presta valve
SEATPOST	PNW Loam OE Dropper, tool-less travel adjust, Range lever, 34.9, S1: 125mm, S2: 150mm, S3: 170mm, S4-S6: 200mm
SEAT BINDER	Alloy, 38.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
93325-3101	SJ 15 EXPERT GUN/WHTMTN S1	Gloss Gunmetal / White Mountai	S1 29/27.5
93325-3102			S2 29/27.5
93325-3103			S3 29
93325-3104			S4 29
93325-3105			S5 29
93325-3106			S6 29
93325-3001	SJ 15 EXPERT EGRN/FSTGRN S1	Satin Electric Green / Satin Forest Green	S1 29/27.5
93325-3002			S2 29/27.5

STUMPJUMPER 15 EXPERT

PART NO.	DESCRIPTION	COLOR	SIZE
93325-3003	SJ 15 EXPERT EGRN/FSTGRN S3	Satin Electric Green / Satin F	S3 29
93325-3004			S4 29
93325-3005			S5 29
93325-3006			S6 29

STUMPJUMPER 15 PRO



Satin Green Tint / Gunmetal / Satin Metallic Sulphur

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis and rear-end
- Super-light and durable Roval Traverse SL wheels, Industry Nine 1/1 hub
- Ride Dynamics tuned FOX FLOAT Performance Elite with Specialized GENIE patent-pending air spring technology provides maximum grip and traction found in a linear coil spring, bottom-out prevention found in a progressive air spring, and the ability to tune mid-stroke and end-stroke support independently. Highly adjustable 2-position open and firm mode with the 3-position open mode compression adjuster.
- Supportive and tuneable FOX FLOAT 36 Factory fork with GRIP X2 damper
- Smooth and precise SRAM XO Eagle T-Type AXS drivetrain
- Big stopping power from SRAM Maven Silver, 4-piston brakes
- Slam your saddle with Bike Yoke Revive Max's ultra-low stack dropper post
- Lifetime bearing replacement

STUMPJUMPER 15 PRO	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Headtube Length (mm)	95	100	110	125	140	155
Headtube Angle (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Fork Length (full) (mm)	551	561	561	561	561	561
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	720	751	780	812	843	879
Chainstay Length (mm)	430	432	435	435	445	445
Wheelbase (mm)	1149	1181	1213	1244	1285	1322
Top-tube Length (horizontal) (mm)	541	573	595	624	647	677
Bike Standover Height (mm)	738	751	745	745	745	751
Seat Tube Length (mm)	385	385	405	425	445	465
Seat Tube Angle (degrees)	77	76.5	77.2	76.9	77.3	77.6
Max Seatpost Insertion (mm)	245	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	165	165	165	170	170	170
Handlebar Width (mm)	780	780	800	800	800	800
Stem Length (mm)	40	40	40	40	40	40
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	125	160	185	185	213	213

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m carbon chassis and rear-end, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
FORK	FOX FLOAT 36 Factory, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
STEM	Industry 9 Mountain stem, 35mm clamp, 40mm length
HANDLEBARS	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S1-S2: 780mm; S3-S6: 800mm
GRIPS	Deity Lockjaw
FRONT BRAKE	SRAM Maven Silver, 4-piston caliper, hydraulic disc, 200mm
REAR BRAKE	SRAM Maven Silver, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm
SHIFT LEVERS	SRAM AXS POD Controller
REAR DERAILLEUR	SRAM XO Eagle Transmission Derailleur
CASSETTE	SRAM XO Eagle Transmission Cassette, 12spd, 10-52t
CHAIN	SRAM XO Eagle Transmission Flattop Chain
CRANKSET	SRAM XO Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
BOTTOM BRACKET	SRAM DUB, BSA 73mm Wide, Threaded
RIMS	Roval Traverse SL, hookless carbon, 30mm inner width, tubeless ready, Front: 29, Rear: S1-S2: 27.5, S3-S6: 29
FRONT HUB	Industry 9 1/1, 15x110mm, 28h
REAR HUB	Industry 9 1/1, 12x148mm, 28h
SPOKES	Sapim D-Light
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
INNER TUBES	Standard, Presta valve
SADDLE	Bridge Expert with MIMIC, Hollow Ti rails, S1-S2: 155mm, S3-S6: 143mm
SEATPOST	Bike Yoke, Revive Max, 34.9, S1: 125mm, S2: 160mm, S3-S4: 185mm, S5-S6: 213mm
SEAT BINDER	Alloy, 38.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
93325-1001	SJ 15 PRO GRNTNT/GUN/METSLPHR S1	Satin Green Tint / Gunmetal	\$1 29/27.5
93325-1002			S2 29/27.5
93325-1003			S3 29
93325-1004			S4 29
93325-1005			S5 29
93325-1006			S6 29

S-WORKS STUMPJUMPER 15



IMAGE
coming soon

Satin Gunmetal / Clay / White Mtn / Dove Grey / Gloss Bronze

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis, rear-end, and link
- The lightest high-performance Roval Traverse SL wheels, DT Swiss 240 hub
- Ride Dynamics tuned FOX FLOAT Performance Elite with Specialized GENIE patent-pending air spring technology provides maximum grip and traction found in a linear coil spring, bottom-out prevention found in a progressive air spring, and the ability to tune mid-stroke and end-stroke support independently. Highly adjustable 2-position open and firm mode with the 3-position open mode compression adjuster.
- Supportive and tuneable FOX FLOAT 36 Factory fork with GRIP X2 damper
- Strong and precise SRAM XX Eagle T-Type AXS drivetrain
- Super-powered braking from SRAM Maven Ultimate 4-piston brakes
- Smooth and reliable RockShox Reverb AXS dropper post
- Lifetime bearing replacement

S-WORKS STUMPJUMPER 15	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Headtube Length (mm)	95	100	110	125	140	155
Headtube Angle (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Fork Length (full) (mm)	551	561	561	561	561	561
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	720	751	780	812	843	879
Chainstay Length (mm)	430	432	435	435	445	445
Wheelbase (mm)	1149	1181	1213	1244	1285	1322
Top-tube Length (horizontal) (mm)	541	573	595	624	647	677
Bike Standover Height (mm)	738	751	745	745	745	751
Seat Tube Length (mm)	385	385	405	425	445	465
Seat Tube Angle (degrees)	77	76.5	77.2	76.9	77.3	77.6
Max Seatpost Insertion (mm)	245	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80	80
Crank Length (mm)	165	165	165	170	170	170
Handlebar Width (mm)	780	780	800	800	800	800
Stem Length (mm)	35	35	35	35	35	35
Saddle Width (mm)	155	155	143	143	143	143
Seatpost Length (mm)	125	150	170	170	170	170

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m carbon chassis, rear-end, and link, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
FORK	FOX FLOAT 36 Factory, GRIP X2 damper, HS and LS rebound and compression adjustment, 15x110mm QR axle, 44mm offset, S1:140mm of travel, S2-S6:150mm of travel
STEM	Deity, 35mm clamp, 35mm length
HANDLEBARS	Roval Traverse SL Carbon, riser bar, 6-degree upsweep, 8-degree backsweep, 30mm rise, S1-S2: 780mm; S3-S6: 800mm
GRIPS	Deity Lockjaw
FRONT BRAKE	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, 200mm
REAR BRAKE	SRAM Maven Ultimate, 4-piston caliper, hydraulic disc, S1-S2: 180mm, S3-S6: 200mm
REAR DERAILLEUR	SRAM XX Eagle Transmission Derailleur
SHIFT LEVERS	SRAM AXS POD Ultimate Controller
CASSETTE	SRAM XX Eagle SL Transmission Cassette, 12spd, 10-52t
CHAIN	SRAM XX Eagle SL Transmission Flattop Chain
CRANKSET	SRAM XX Eagle Crankset, 32T ring, Integrated Guard, 55mm Chainline, S1-S3:165mm, S4-S6: 170mm
BOTTOM BRACKET	SRAM DUB, BSA 73mm Wide, Threaded
RIMS	Roval Traverse SL, hookless carbon, 30mm inner width, tubeless ready, 28h, Front: 29, Rear: S1-S2: 27.5, S3-S6: 29
FRONT HUB	DT Swiss 240, 15x110mm, 28h
REAR HUB	DT Swiss 240, 12x148mm, 28h
SPOKES	DT Swiss Aerolite
FRONT TIRE	Butcher, GRID TRAIL casing, GRIPTON® T9 compound, 2Bliss Ready, 29x2.3"
REAR TIRE	Eliminator, GRID TRAIL casing, GRIPTON® T7 compound, 2Bliss Ready, S1-S2: 27.5x2.3, S3-S6: 29x2.3"
SADDLE	Power Pro Mirror, Hollow Ti rails, S1-S2: 155mm, S3-S6: 143mm
INNER TUBES	Standard, Presta valve
SEATPOST	RockShox, Reverb AXS, 30.9, S1: 125mm, S2: 150mm, S3-S6: 170mm
SEAT BINDER	Alloy, 38.6mm

PART NO.	DESCRIPTION	COLOR	SIZE
93325-0001	SJ15 SW GUN/CLY/WHTMTN S1	Satin Gunmetal / Clay / White Mtn	29/27.5
93325-0002			S2 29/27.5
93325-0003			S3 29
93325-0004			S4 29
93325-0005			S5 29
93325-0006			S6 29

S-WORKS STUMPJUMPER 15 FRAMESET



Satin Nrlly Blk / Blk / Cool Grey / Obsidian / Satin Dove Grey

Stumpjumper 15 is here to obliterate every trade-off in the trail game. Devour bumps like a big bike? Check. Short-travel control, playfulness, and efficiency? Double check. How about a heaping helping of personalization to make it perfect for the only rider who really matters—you? Check, check, check.

- Lightweight FACT 11m carbon chassis, rear-end, and link
- Ride Dynamics tuned FOX FLOAT Performance Elite with Specialized GENIE patent-pending air spring technology provides maximum grip and traction found in a linear coil spring, bottom-out prevention found in a progressive air spring, and the ability to tune mid-stroke and end-stroke support independently. Highly adjustable 2-position open and firm mode with the 3-position open mode compression adjuster.
- Lifetime bearing replacement

SPECS	Specifications subject to change without notice.
FRAME	FACT 11m carbon chassis, rear-end and link, Trail Geometry, SWAT™ Door integration, head tube angle adjustment, threaded BB, internal brake and dropper cable routing, 12x148mm dropouts, sealed cartridge bearing pivots, SRAM UDH compatible, 145mm of travel
SWAT	SWAT 4.0 internal downtube storage
REAR SHOCK	FOX FLOAT Factory with Specialized GENIE Shock Tech, Ride Dynamics Trail Tune, 2-position lever w/3 setting Open mode tuning range, LSR adjustment, S1:210x52.5mm, S2-S6:210x55mm
SEAT BINDER	Alloy, 38.6mm

S-WORKS STUMPJUMPER 15 FRAMESET

	S1	S2	S3	S4	S5	S6
Stack (mm)	608	618	627	640	654	667
Reach (mm)	400	425	450	475	500	530
Headtube Length (mm)	95	100	110	125	140	155
Headtube Angle (degrees)	64.5	64.5	64.5	64.5	64.5	64.5
BB Height (mm)	334	337	337	337	337	337
BB Drop (mm)	41	38	38	38	38	38
Trail (mm)	129	130	130	130	130	130
Fork Length (full) (mm)	551	561	561	561	561	561
Fork Rake/Offset (mm)	44	44	44	44	44	44
Front Center (mm)	720	751	780	812	843	879
Chainstay Length (mm)	430	432	435	435	445	445
Wheelbase (mm)	1149	1181	1213	1244	1285	1322
Top-tube Length (horizontal) (mm)	541	573	595	624	647	677
Bike Standover Height (mm)	738	751	745	745	745	751
Seat Tube Length (mm)	385	385	405	425	445	465
Seat Tube Angle (degrees)	77	76.5	77.2	76.9	77.3	77.6
Max Seatpost Insertion (mm)	245	245	255	255	285	285
Min Seatpost Insertion (mm)	80	80	80	80	80	80

PART NO.	DESCRIPTION	COLOR	SIZE
73325-0001	SJ15 SW FRM NRBLK/BLK/CLGRY S1	Satin Nrlly Blk / Blk / Cool Gr	S1 29/27.5
73325-0002			S2 29/27.5
73325-0003			S3 29
73325-0004			S4 29
73325-0005			S5 29
73325-0006			S6 29